

FEATURES



A. LUMBAR SUPPORT

Static Lumbar Support Located at 5.5" to 18" above compressed seat height. Built-in integral flex lumbar adjusting spring that self adjusts to each user individually.

B. MECHANISM

Swivel Mechanism with pneumatic height adjustment, infinite position tilt lock, tilt tension and seat depth adjustment.

C. BACK AND SEAT

Upholstered seat and back made with high density molded foam. Ratchet height adjustable back that is contoured for ergonomic support and comfort. Seat features a water fall edge to promote proper circulation.

D. ARMS

Ratchet height and width adjustable arms with super soft, lockable, pivoting polyurethane arm pads. 4" height, 3" width and 30° pivot range of motion.

E. BASE AND CASTERS

5 prong heavy duty nylon base with dual wheel carpet casters.

Note: multiple aesthetic and functional options available.

Model 1600

Overall Width (Outer armrest to outer armrest)	27" - 29.5"
Overall Depth (Front seat to back of back rest)	22" - 25"
Overall Height (Floor to top of back rest)	38" - 44"
Seat Width	20"
Back Width	19"
Back Height (From compressed seat)	20.5" - 23"
Arm Width (Inner arm pad to inner arm pad)	18.5" - 21.5"
Arm Height (Compressed seat to top of armrest)	7" - 11"
Seat Height	16" - 21"
Seat Depth	16.8" - 19.8"



Model 1600D

Overall Width (Outer armrest to outer armrest)	27" - 29.5"
Overall Depth (Front seat to back of back rest)	22" - 25"
Overall Height (Floor to top of back rest)	43.5" - 47"
Seat Width	21.5"
Back Width	20"
Back Height (From compressed seat)	26" - 28.5"
Arm Width (Inner arm pad to inner arm pad)	18.5" - 21.5"
Arm Height (Compressed seat to top of armrest)	7" - 11"
Seat Height	16" - 21"
Seat Depth	17.2" - 20.3"

